MATERIAL SAFETY DATA SHEET
FC Adhesive (Concentrate)

Section 1-MATERIAL IDENTIFICATION AND USE

MANUFACTURER'S NAME ..... International Cellulose Corporation

MANUFACTURER'S ADDRESS ..... 12315 Robin Blvd.
Houston, TX 77045

EMERGENCY PHONE NUMBER ..... (713) 433-6701

INFORMATION PHONE NUMBER ..... (713) 433-6701

SUPPLIER IDENTIFIER ..... International Cellulose Corporation

SUPPLIER'S ADDRESS ..... 12315 Robin Blvd.
Houston, TX 77045

SUPPLIER EMERGENCY PHONE NUMBER ..... (713) 433-6701

PRODUCT IDENTIFIER ..... FC Adhesive (Concentrate)

PRODUCT USE ..... Adhesive

Section 2-HAZARDOUS INGREDIENTS OF MATERIALS

Chemical Identity	Concentration	CAS Registry #
Vinyl Acrylic Latex	≤55 % by wt.	108-05-4

Section 3-PHYSICAL DATA FOR PRODUCT

PHYSICAL STATE ..... LIQUID
ODOUR AND APPEARANCE ..... Milky White, slight acrylic
ODOUR THRESHOLD ..... NO DATA
SPECIFIC GRAVITY 1.08
VAPOUR PRESSURE ..... Same as water
VAPOUR DENSITY (air = 1) ..... Same as water
EVAPORATION RATE ..... Same as water
BOILING POINT ..... 212°C
FREEZING POINT ..... Not established
pH 4.5
WEIGHT per GALLON ..... 8.9 lbs.
SOLUBILITY IN WATER ..... Dispersible

Section 4-FIRE AND EXPLOSION HAZARD OF PRODUCT

CONDITIONS OF FLAMMABILITY ..... NOT FLAMMABLE IN LIQUID STATE
MEANS OF EXTINCTION ..... CO2, foam, dry chemical powder, water.
FLASH POINT & METHOD OF DETERMINATION ..... NOT FLAMMABLE
UPPER EXPLOSION LIMIT (% BY VOL) ..... NOT APPLICABLE
LOWER EXPLOSION LIMIT (% BY VOL) ..... NOT APPLICABLE
AUTO-IGNITION TEMPERATURE ..... NO DATA
FLAMMABILITY CLASSIFICATION ..... NOT FLAMMABLE
HAZARDOUS COMBUSTION PRODUCTS ..... Low molecular weight hydrocarbons, carbon monoxide
EXPLOSION DATA ..... Pressure build-up possible in closed containers when heated. Water spray may be used to cool containers.
SENSITIVITY TO STATIC DISCHARGE ..... NO DATA.
SPECIAL FIRE FIGHTING PROCEDURE ..... Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.