

MATERIAL SAFETY DATA SHEET

SK2000

Section 1-MATERIAL IDENTIFICATION AND USE

MANUFACTURER'S NAMEInternational Cellulose Corporation
MANUFACTURER'S ADDRESS12315 Robin Blvd.
Houston, TX 77045
EMERGENCY PHONE NUMBER(713) 433-6701
INFORMATION PHONE NUMBER.....(713) 433-6701
SUPPLIER IDENTIFIERInternational Cellulose Corporation
SUPPLIER'S ADDRESS.....12315 Robin Blvd.
Houston, TX 77045
SUPPLIER EMERGENCY PHONE NUMBER(713) 433-6701
PRODUCT IDENTIFIER..... SK2000
PRODUCT USE.....Adhesive Binder

Section 2-COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity	Concentration	CAS Registry #
Poly Vinyl Alcohol	≤ 5% by wt.	9002-89-5
Copolymer	≤ 50% by wt.	

Section 3-PHYSICAL DATA FOR PRODUCT

PHYSICAL STATELIQUID
ODOUR AND APPEARANCESlightly sweet, viscous clear
SPECIFIC GRAVITY1.08
VAPOUR PRESSURE.....Same as water
VAPOUR DENSITY (air = 1)Same as water
EVAPORATION RATESame as water
BOILING POINT212°C
FREEZING POINTNot established
pH4.0-9.0
WEIGHT per GALLON9.1 lbs.
SOLUBILITY IN WATERDispersible

Section 4-FIRE AND EXPLOSION HAZARD OF PRODUCT

CONDITIONS OF FLAMMABILITYNOT FLAMMABLE IN LIQUID STATE
MEANS OF EXTINCTIONCO2, foam, dry chemical powder, water.
FLASH POINT & METHOD OF DETERMINATIONNOT FLAMMABLE
UPPER EXPLOSION LIMIT (% BY VOL).....NOT APPLICABLE
LOWER EXPLOSION LIMIT (% BY VOL).....NOT APPLICABLE
AUTO-IGNITION TEMPERATURENO DATA
FLAMMABILITY CLASSIFICATIONNOT FLAMMABLE
HAZARDOUS COMBUSTION PRODUCTSCarbon monoxide/dioxide
EXPLOSION DATAPressure build-up possible in closed containers when heated. Water spray may be used to cool containers.
SENSITIVITY TO STATIC DISCHARGENO DATA.
SPECIAL FIRE FIGHTING PROCEDUREPersons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

